reolink	Reolink Innovation Limimted.		
Picture			
Model	**Go Series G430**		
Video & Audio	Image Sensor		1/3" CMOS Sensor
	Video Resolution		2880 x 1620 (5.0Megapixel) at 15 frames/sec
	Video Format		H.265
	Field of View		Fixed lens, Horizontal: 90°, Vertical: 47°, 110° diagonal
	Infrared Night Vision		up to 10 Meters (33ft) (LED: 2pcs/1.2W/850nm)
	Spotlight		2pcs/2.4W/6500K/
	Digital Zoom		16x digital zoom
	Audio		two-way audio
PIR Detection & Alerts	Smart Alarm		PIR detection/Human Detection/Vehicle Detection/Animal Detecti
	PIR Detecting Distance		Adjustable up to 10m (33 ft)
	PIR Detecting Angle		120° horizontal
	Audio Alert		Customized verbal alerts
	Recording		Motion Triggered Recording
	Other Alerts		Instant email alerts and push notifications
3G/4G	Frequency Bands	Europe	LTE FDD: B1/B3/B7/B8/B20/B28A
			WCDMA: B1/B8
		America	LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
			WCDMA: B2/B4/B5
		Australia	LTE FDD: B1/B3/B5/B7/B8/B28
			LTE TDD: B40
			WCDMA: B1/B5/B8
	Transmission Data		LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)
			LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)
			HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)
			UMTS: Max 384Kbps(DL), Max 384Kbps(UL)
Power	Battery		6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar		Reolink Solar Panel
	DC Power		5V/2A USB power adaptor
Storage	Local Storage		Supports up to 128GB micro SD card
	Cloud Storage		Supports Reolink Cloud
Smart Home	Smart Home		Works with Google Assistant
Working Environment	Operating Temperature		-10 to 55° C (14° to 131° F)
	Weather Resistance		IP64 Weatherproof
Size & Weight	Size		Φ98 x 122mm (Φ3.7 x 4.4 in)
	Weight (Battery included)		485 g (17.1 oz)
Warranty	Limited Warranty		2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/